


Window Units

Climatcool U.S.A.
Hi-Tech Airconditioning

Washable Filter >>

► Patented disassembling technology offers easier detachment, so the filter mesh can be cleaned at will.



Self-evaporative System >>

► The slinger-up system automatically recycle condensate water of evaporator to condenser, no need of water bucket. It can bring more cooling power and improve cooling efficiency.

Ventilation >>

► With the present fresh air outlet, the fresh air can be brought from outside to the room to improve indoor air quality and create a new & comfortable atmosphere.



Specification



T3, High Efficiency, R-410a

| Unit Model | | SCWT-18CAN1 | SCWT-24CAN1 |
|---------------------------|---------------------|----------------------------|----------------------------|
| Power Supply | | V,Hz,Ph | |
| | | 220-240V/ 50Hz/ 1Ph | |
| Cooling | Capacity (T1/T3) | Btu/h | 17500 / 14700 |
| | | Kw | 5.13 / 4.31 |
| | Power Input (T1/T3) | Kw | 1.80 / 2.10 |
| | Current (T1/T3) | A | 8.5 / 10.5 |
| | EER (T1/T3) | (Btu/H)/W | 9.7 / 7.0 |
| Evaporator Side | Controller | Type | Mechanical (Analogue) Type |
| | Air Flow (H/M/L) | m ³ /h | 750/650/550 |
| | Noise Level (H/M/L) | dB(A) | 56/53/50 |
| Condenser Side | Compressor | Type | Rotary |
| | Tube | Type | Internal Threaded Tube |
| | Refrigerant | Type | R-410a |
| Net Dimension (WxHxD) | | mm | 660x435x690 |
| Packing Dimension (WxHxD) | | mm | 740x512x770 |
| Net/ Gross Weight | | Kg | 53/57 |
| Operation Temp. | | °C | 18-30 |
| Ambient Temp. | | °C | 18-52 |
| Stuffing Quantity (40'HQ) | | Pcs. | 225 |

Note:

- The Above design and specification are subject to change without prior notice.
- Cooling conditions; T1: Indoor air temp. 27°C DB/19°C WB, Outdoor air temp. 35°C Db.
T3: Indoor air temp. 27°C DB/19°C WB, Outdoor air temp. 46°C Db.